

SBC Miniature Bearing 微型球轴承

基本尺寸(mm)					轴承型号			额定载荷(N)		极限转速(rpm)		重量(g)	
principal dimensions					Bearing No.			Basic load ratings		Speed ratings		weight	
d	D	B	B1	r(min)	open	shielded	sealed	dynamic (Cr)	static (Cor)	脂 (grease)	油(oil)	Open	shielded
2	5	1.5	2.3	0.08	682	682ZZ	-	169	50	85000	100000	0.12	0.17
	5	2	2.5	0.1	MR52	MR52ZZ	-	169	50	85000	100000	0.16	0.23
	6	2.3	3	0.15	692	692ZZ	-	330	98	75000	90000	0.28	0.38
	6	2.5	2.5	0.15	MR62	MR62ZZ	-	330	98	75000	90000	0.3	0.29
	7	2.5	3	0.15	MR72	MR72ZZ	-	385	127	63000	75000	0.45	0.49
3	6	1.8	2.6	0.08	682X	682XZZ	-	208	74	71000	80000	0.23	0.29
	7	2.5	3.5	0.15	692X	692XZZ	-	385	127	63000	75000	0.41	0.55
	8	2.5	-	0.2	MR82X	-	-	560	179	60000	67000	0.56	-
	8	2.8	4	0.15	602X	602XZZ	-	550	175	60000	71000	0.63	0.83
3	6	2	2.5	0.1	MR63	MR63ZZ	-	208	74	71000	80000	0.2	0.27
	7	2	3	0.1	683	683ZZ	-	310	111	63000	75000	0.32	0.45
	8	2.5	-	0.15	MR83	-	-	560	179	60000	67000	0.54	-
	8	3	4	0.15	693	693ZZ	-	560	179	60000	67000	0.61	0.83
	9	2.5	4	0.2	MR93	MR93ZZ	-	570	187	56000	67000	0.73	1.18
	9	3	-	0.15	603	-	-	570	187	56000	67000	0.87	-
	10	4	4	0.15	623	623ZZ	-	630	218	50000	60000	1.65	1.66
	13	5	5	0.2	633	633ZZ	-	1300	485	40000	48000	3.38	3.33
4	7	2	2.5	0.1	MR74	MR74ZZ	-	310	115	60000	67000	0.22	0.29
	8	2	3	0.15	MR84	MR84ZZ	-	395	139	56000	67000	0.36	0.56
	9	2.5	4	0.1	684	684ZZ	-	640	225	53000	63000	0.63	1.01
	10	3	4	0.2	MR104	MR104ZZ	-	585	204	48000	56000	0.95	1.36
	11	4	4	0.15	694	694ZZ	-	960	345	48000	56000	1.7	1.75
	12	4	4	0.2	604	604ZZ	-	960	345	48000	56000	2.25	2.29
	13	5	5	0.2	624	624ZZ	-	1300	485	40000	48000	3.03	3.04
	16	5	5	0.3	634	634ZZ	-	1730	670	36000	43000	5.24	5.21
5	8	2	2.5	0.1	MR85	MR85ZZ	-	310	120	53000	63000	0.26	0.34
	9	2.5	3	0.15	MR95	MR95ZZ	-	430	168	50000	60000	0.5	0.58
	10	3	4	0.15	MR105	MR105ZZ	-	430	168	50000	60000	0.95	1.29
	11	3	5	0.15	685	685ZZ	-	715	281	45000	53000	1.2	1.96
	13	4	4	0.2	695	695ZZ	2RS	1080	430	43000	50000	2.45	2.5
	14	5	5	0.2	605	605ZZ	-	1330	505	40000	50000	3.54	3.48
	16	5	5	0.3	625	625ZZ	2RS	1730	670	36000	43000	4.95	4.86
	19	6	6	0.3	635	635ZZ	2RS	2340	885	32000	40000	8.56	8.34
6	10	2.5	3	0.15	MR106	MR106ZZ	-	495	218	45000	53000	0.56	0.68
	12	3	4	0.2	MR126	MR126ZZ	-	715	292	43000	50000	1.27	1.74
	13	3.5	5	0.15	686	686ZZ	-	1080	440	40000	50000	1.91	2.69
	15	5	5	0.2	696	696ZZ	2RS	1730	670	40000	45000	3.88	3.72

SBC Miniature Bearing 微型球轴承

基本尺寸(mm)					轴承型号			额定载荷(N)		极限转速(rpm)		重量(g)	
principal dimensions					Bearing No.			Basic load ratings		Speed ratings		weight	
d	D	B	B1	r(min)	open	shielded	sealed	dynamic (Cr)	static (Cor)	脂 (grease)	油(oil)	Open	shielded
	17	6	6	0.3	606	606ZZ	2RS	2260	835	32000	40000	8.15	7.94
	19	6	6	0.3	626	626ZZ	2RS	2340	885	32000	40000	8.15	7.94
	22	7	7	0.3	636	636ZZ	-	3300	1370	30000	36000	14	14
7	11	2.5	3	0.15	MR117	MR117ZZ	-	455	201	43000	50000	0.62	0.72
	13	3	4	0.2	MR137	MR137ZZ	-	540	276	40000	48000	1.58	2.02
	14	3.5	5	0.15	687	687ZZ	2RS	1170	510	40000	45000	2.13	2.97
	17	5	5	0.3	697	697ZZ	-	1610	710	36000	43000	5.26	5.12
	19	6	6	0.3	607	607ZZ	2RS	2340	885	36000	43000	7.67	7.51
	22	7	7	0.3	627	627ZZ	2RS	3300	1370	30000	36000	12.7	12.9
	26	9	9	0.3	637	637ZZ	2RS	4050	1620	28000	34000	24	25
8	12	2.5	3.5	0.15	MR128	MR128ZZ	-	545	275	40000	48000	0.71	0.97
	14	3.5	4	0.2	MR148	MR148ZZ	-	820	385	38000	45000	1.86	2.16
	16	4	5	0.2	688	688ZZ	2RS	1260	590	36000	43000	3.25	4
	19	6	6	0.3	698	698ZZ	2RS	2240	910	36000	43000	7.23	7.18
	22	7	7	0.3	608	608ZZ	2RS	3300	1370	34000	40000	12.1	12.2
	24	8	8	0.3	628	628ZZ	2RS	3350	1430	28000	34000	17.2	17.4
	28	9	9	0.3	638	638ZZ	-	4550	1970	28000	34000	28.3	28.6
9	17	4	5	0.2	689	689ZZ	2RS	1330	665	36000	43000	3.53	4.43
	20	6	6	0.3	699	699ZZ	-	1720	840	34000	40000	8.45	8.33
	24	7	7	0.3	609	609ZZ	2RS	3350	1430	32000	38000	14.5	14.7
	26	8	8	0.3	629	629ZZ	2RS	4550	1970	28000	34000	19.5	19.3
	30	10	10	0.6	639	639ZZ	2RS	5100	2390	24000	30000	36.5	36