



## SBC Single Row Angular Contact Ball Bearing 单列角接触球轴承

基本尺寸(mm)					轴承型号	额定载荷(N)		极限转速(rpm)		重量(kg)
principal dimensions					Bearing No.	Basic load ratings		Speed ratings		weight
d	D	B	B1	r(min)		dynamic (Cr)	static (Cor)	脂(grease)	油(oil)	
10	26	8	0.3	0.15	7000C	4920	2250	19000	28000	0.018
	26	8	0.3	0.15	7000AC	4750	2120	19000	28000	0.018
	30	9	0.6	0.3	7200C	5820	2950	18000	26000	0.03
	30	9	0.6	0.3	7200AC	5580	2820	18000	26000	0.03
	30	9	0.6	0.3	7200B	5580	2820	18000	26000	0.03
12	28	8	0.3	0.15	7001C	5420	2650	18000	26000	0.02
	28	8	0.3	0.15	7001AC	5200	2550	18000	26000	0.02
	32	10	0.6	0.3	7201C	7350	3520	17000	24000	0.035
	32	10	0.6	0.3	7201AC	7100	3350	17000	24000	0.035
	32	10	0.6	0.3	7201B	7100	3300	17000	24000	0.035
	37	12	0.6	0.3	7301B	9600	4000	16000	22000	0.06
15	32	9	0.3	0.15	7002C	6250	3420	17000	24000	0.028
	32	9	0.3	0.15	7002AC	5950	3250	17000	24000	0.028
	35	11	0.6	0.3	7202C	8680	4620	16000	22000	0.043
	35	11	0.6	0.3	7202AC	8350	4400	16000	22000	0.043
	35	11	0.6	0.3	7202B	8300	4300	16000	22000	0.043
	42	13	1	0.6	7302B	12000	6000	14000	19000	0.08
17	35	10	0.3	0.15	7003C	6600	3850	16000	22000	0.036
	35	10	0.3	0.15	7003AC	6300	3680	16000	22000	0.036
	40	12	0.6	0.3	7203C	10800	5950	15000	20000	0.062
	40	12	0.6	0.3	7203AC	10500	5650	15000	20000	0.062
	40	12	0.6	0.3	7203B	9950	5500	14000	19000	0.062
	47	14	1	0.6	7303B	14000	8000	13000	18000	0.11
20	42	12	0.6	0.3	7004C	10500	6080	14000	19000	0.064
	42	12	0.6	0.3	7004AC	10000	5780	14000	19000	0.064
	47	14	1	0.6	7204C	14500	8220	13000	18000	0.1
	47	14	1	0.6	7204AC	14000	7820	13000	18000	0.1
	47	14	1	0.6	7204B	14000	7850	13000	18000	0.11
	52	15	1	0.6	7304B	17300	9650	11000	15000	0.14
25	47	12	0.6	0.3	7005C	11500	7450	12000	17000	0.074
	47	12	0.6	0.3	7005AC	11200	7080	12000	17000	0.074
	52	15	1	0.6	7205C	16500	10500	11000	16000	0.12
	52	15	1	0.6	7205AC	15800	9880	11000	16000	0.12
	52	15	1	0.6	7205B	15800	9450	9500	14000	0.13
25	62	17	1.1	0.6	7305B	26200	15200	8500	12000	0.3
30	55	13	1	0.6	7006C	15200	10200	9500	14000	0.11



## SBC Single Row Angular Contact Ball Bearing 单列角接触球轴承

基本尺寸(mm)					轴承型号	额定载荷(N)		极限转速(rpm)		重量(kg)
principal dimensions					Bearing No.	Basic load ratings		Speed ratings		weight
d	D	B	B1	r(min)		dynamic (Cr)	static (Cor)	脂(grease)	油(oil)	
	55	13	1	0.6	7006AC	14500	9850	9500	14000	0.11
	62	16	1	0.6	7206C	23000	15000	9000	13000	0.19
	62	16	1	0.6	7206AC	22000	14200	9000	13000	0.19
	62	16	1	0.6	7206B	20500	13800	8500	12000	0.21
	72	19	1.1	0.6	7306B	31000	19200	7500	10000	0.37
35	62	14	1	0.6	7007C	19500	14200	8500	12000	0.15
	62	14	1	0.6	7007AC	18500	13500	8500	12000	0.15
	72	17	1.1	0.6	7207C	30500	20000	8000	11000	0.28
	72	17	1.1	0.6	7207AC	29000	19200	8000	11000	0.28
	72	17	1.1	0.6	7207B	27000	18800	7500	10000	0.3
	80	21	1.5	0.6	7307B	38200	24500	7000	9500	0.51
40	68	15	1	0.3	7008C	20000	15200	8000	11000	0.18
	68	15	1	0.6	7008AC	19000	14500	8000	11000	0.18
	80	18	1.1	0.6	7208C	36800	25800	7500	10000	0.37
	80	18	1.1	0.6	7208AC	35200	24500	7500	10000	0.37
	80	18	1.1	0.6	7208B	35200	23500	6700	9000	0.39
	90	23	1.5	0.6	7308B	46200	30500	6300	8500	0.67
	110	27	2	1	7408B	67000	47500	6000	8500	1.4
45	75	16	1	0.6	7009C	25800	20500	7500	10000	0.23
	75	16	1	0.6	7009AC	25800	19500	7500	10000	0.23
	85	19	1.1	0.6	7209C	38500	28500	6700	9000	0.41
	85	19	1.1	0.6	7209AC	36800	27200	6700	9000	0.41
	85	19	1.1	0.6	7209B	36000	26200	6300	8500	0.44
	100	25	1.5	0.6	7309B	59500	39800	6000	8500	0.9
50	80	16	1	0.6	7010C	26500	22000	6700	9000	0.25
	80	16	1	0.6	7010AC	25200	21000	6700	9000	0.25
	90	20	1.1	0.6	7210C	42800	32000	6300	8500	0.46
	90	20	1.1	0.6	7210AC	40800	30500	6300	8500	0.46
	90	20	1.1	0.6	7210B	37500	29000	5600	7500	0.49
	110	27	2	0.6	7310B	68200	48000	5000	6700	1.15
	130	31	2.1	0.6	7410B	95200	64200	5000	6700	2.08
55	90	18	1.1	0.6	7011C	37200	30500	6000	8000	0.38
	90	18	1.1	0.6	7011AC	35200	29200	6000	8000	0.38
	100	21	1.5	0.6	7211C	52800	40500	5600	7500	0.61
	100	21	1.5	0.6	7211AC	50500	38500	5600	7500	0.61
	100	21	1.5	0.6	7211B	46200	36000	5300	7000	0.65
	120	29	2	1	7311B	78800	56500	4500	6000	1.45





## SBC Single Row Angular Contact Ball Bearing 单列角接触球轴承

基本尺寸(mm)					轴承型号	额定载荷(N)		极限转速(rpm)		重量(kg)
principal dimensions					Bearing No.	Basic load ratings		Speed ratings		weight
d	D	B	B1	r(min)		dynamic (Cr)	static (Cor)	脂(grease)	油(oil)	
90	140	24	1.5	0.6	7018C	71500	69800	4000	5300	1.15
	140	24	1.5	0.6	7018AC	67500	66500	4000	5300	1.15
	160	30	2	1	7218C	122000	105000	3600	4800	2.25
	160	30	2	1	7218AC	118000	100000	3600	4800	2.25
	160	30	2	1	7218B	105000	94500	3200	4300	2.4
	190	43	3	1.1	7318B	158000	138000	2800	3800	5.4
95	145	24	1.5	0.6	7019C	73500	73200	3800	5000	1.2
	145	24	1.5	0.6	7019AC	69500	69800	3800	5000	1.2
	170	32	2.1	1.1	7219C	135000	115000	3400	4500	2.7
	170	32	2.1	1.1	7219AC	128000	108000	3400	4500	2.7
	170	32	2.1	1.1	7219B	120000	108000	3000	4000	2.9
	200	45	3	1.1	7319B	172000	155000	2800	3800	6.25
100	150	24	1.5	0.6	7020C	79200	78500	3800	5000	1.25
	150	24	1.5	0.6	7020AC	75000	74800	3800	5000	1.25
	180	34	2.1	1.1	7229C	148000	128000	3200	4300	3.25
	180	34	2.1	1.1	7220AC	142000	122000	3200	4300	3.25
	180	34	2.1	1.1	7220B	130000	115000	2600	3600	3.45
	215	47	3	1.1	7320B	188000	180000	2400	3400	7.75
105	160	26	2	1	7021C	88500	8800	3600	4800	1.6
	160	26	2	1	7021AC	83800	84200	3600	4800	1.6
	190	36	2.1	1.1	7221C	162000	145000	3000	4000	3.85
	190	36	2.1	1.1	7221AC	155000	138000	3000	4000	3.85
	190	36	2.1	1.1	7221B	142000	130000	2600	3600	4.1
	225	49	3	1.1	7321B	202000	195000	2200	3200	8.8
110	170	28	2	1	7022C	100000	102000	3600	4800	1.95
	170	28	2	1	7022AC	95500	97200	3600	4800	1.95
	200	38	2.1	1.1	7222C	175000	162000	2800	3800	4.55
	200	38	1.1	2.1	7222AC	168000	155000	2800	3800	4.55
	200	38	2.1	1.1	7222B	155000	145000	2400	3400	4.8
	240	50	3	1.1	7322B	225000	225000	2000	3000	10.5
120	180	28	2	1	7024C	108000	110000	2800	3800	2.1
	180	28	2	1	7024AC	102000	105000	2800	3800	2.1
	215	40	2.1	1.1	7224C	188000	180000	2400	3400	5.4
	215	40	2.1	1.1	7224AC	180000	172000	2400	3400	5.4
130	200	33	2	1	7026C	128000	135000	2600	3600	3.2
	200	33	2	1	7026AC	122000	128000	2600	3600	3.2
	230	40	3	1.1	7226C	205000	210000	2200	3200	6.25



## SBC Single Row Angular Contact Ball Bearing 单列角接触球轴承

基本尺寸(mm)					轴承型号	额定载荷(N)		极限转速(rpm)		重量(kg)
principal dimensions					Bearing No.	Basic load ratings		Speed ratings		weight
d	D	B	B1	r(min)		dynamic (Cr)	static (Cor)	脂(grease)	油(oil)	
	230	40	3	1.1	7226AC	195000	200000	2200	3200	6.25
140	210	33	2	1	7028C	140000	145000	2400	3400	3.62
	210	33	2	1	7028AC	140000	150000	2200	3200	3.62
	250	42	3	1.1	7228C	230000	245000	1900	2800	9.36
	250	42	3	1.1	7228AC	230000	235000	1900	2800	9.24
	300	62	4	1.5	7328B	288000	315000	1700	2400	22.44
150	225	35	2.1	1.1	7030C	160000	155000	2200	3200	4.83
	225	35	2.1	1.1	7030AC	152000	168000	2000	3000	4.83
160	290	48	3	1.1	7232C	262000	298000	1700	2400	14.5
	290	48	3	1.1	7232AC	248000	278000	1700	2400	14.5
170	260	42	2.1	1.1	7034AC	192000	222000	1800	2600	8.25
	310	52	4	1.5	7234C	322000	390000	1600	2200	19.2
	310	52	4	1.5	7234AC	305000	368000	1600	2200	17.2
180	320	52	4	1.5	7236C	335000	415000	1500	2000	18.1
	320	52	4	1.5	7236AC	315000	388000	1500	2000	18.1
190	290	46	2.1	1.1	7038AC	215000	262000	1600	2200	10.7
200	310	51	2.1	1.1	7040AC	252000	325000	1500	2000	14.04
	360	58	4	1.5	7240C	360000	475000	1300	1800	25.2
	360	58	4	1.5	7240AC	345000	448000	1300	1800	25.2
220	400	65	4	1.5	7244AC	358000	482000	1100	1600	38.5