

SBC Double Row Angular Contact Ball Bearing 双列角接触球轴承

基本尺寸(mm)				轴承型号			额定载荷(N)		极限转速(rpm)		重量(kg)
Principal dimensions				Bearing No.			Basic load ratings		Speed ratings		weight
d	D	B	r _(min)	open	shielded	sealed	dynamic (Cr)	static (Cor)	脂(grease)	油(oil)	
10	30	14.3	0.6	3200	ZZ	2RS	7420	4300	16333	22000	0.054
12	32	15.9	0.6	3201	ZZ	2RS	10200	5600	15000	20000	0.058
15	35	15.9	0.6	3202	ZZ	2RS	11200	6800	12000	17000	0.066
	42	19	0.6	3302	ZZ	2RS	15100	9150	10000	15000	0.13
17	40	17.5	0.6	3203	ZZ	2RS	14000	8650	10000	15000	0.1
	47	22.2	0.6	3303	ZZ	2RS	21200	12500	9500	14000	0.18
20	47	20.6	1	3204	ZZ	2RS	18500	12000	9000	13000	0.16
	52	22.2	1.1	3304	ZZ	2RS	22200	14200	8500	12000	0.22
25	52	20.6	1	3205	ZZ	2RS	20200	14000	8000	11000	0.18
	62	25.4	1.1	3305	ZZ	2RS	31200	20800	7500	10000	0.35
30	62	23.8	1	3206	ZZ	2RS	25200	20000	7000	9500	0.29
	72	30.2	1.1	3306	ZZ	2RS	36800	28500	6300	8500	0.53
35	72	27	1.1	3207	ZZ	2RS	33500	27500	6000	8000	0.44
	80	30.2	1.1	3306	ZZ	2RS	36800	28500	6300	8500	0.53
40	80	30.2	1.1	3208	ZZ	2RS	40500	33500	5600	7500	0.58
	90	36.5	1.5	3308	ZZ	2RS	53200	43000	5000	6700	0.95
45	85	30.2	1.1	3209	ZZ	2RS	42800	38000	5000	6700	0.63
	100	39.7	1.5	3309	ZZ	2RS	64800	73500	4500	6000	1.4
50	90	30.2	1.1	3210	ZZ	2RS	42800	39000	4800	6300	0.66
	110	44.04	2	3310	ZZ	2RS	79200	96500	4000	5300	1.95
55	100	33.3	1.5	3211	ZZ	2RS	51500	67000	4300	5600	1.05
	120	49.2	2	3300	ZZ	2RS	85800	108000	3800	5000	2.55
60	110	36.5	1.5	3212	ZZ	2RS	65000	85000	3800	5000	1.4
	130	54	2.1	3312	ZZ	2RS	100000	128000	3400	4500	3.25
65	120	38.1	1.5	3213	ZZ	2RS	70200	9500	3600	4800	1.75
	140	58.7	2.1	3313	ZZ	2RS	115000	150000	3200	4300	4.1
70	125	39.7	1.5	3214	ZZ	2RS	68800	98000	3200	4300	1.9
	150	63.5	2.1	3314	ZZ	2RS	132000	172000	2800	3800	5.05
75	130	41.3	1.5	3215	ZZ	2RS	75800	110000	3200	4300	2.1
	160	68.3	2.1	3315	ZZ	2RS	142000	185000	2600	3600	6.15
80	140	44.4	2	3216	-	-	90800	135000	2800	3800	2.65
	170	68.3	2.1	3316	-	-	158000	212000	2400	3400	6.95
85	150	49.2	2	3217	-	-	98000	145000	2600	3600	3.4
	180	73	3	3317	-	-	175000	240000	2200	3200	8.3
90	160	52.4	2	3218	-	-	115000	172000	2400	3400	4.15
	190	73	3	3318	-	-	198000	285000	2000	3000	9.25
95	170	55.6	2.1	3219	-	-	132000	205000	2200	3200	5
	200	77.8	3	3319	-	-	215000	315000	1900	2800	11
100	180	60.3	2.1	3220	-	-	142000	220000	2000	3000	6.1
	215	82.6	3	3320	-	-	230000	355000	1800	2600	13.5
110	200	69.8	2.1	3222	-	-	170000	270000	1900	2800	8.8
	240	92.1	3	3322	-	-	262000	425000	1700	2400	19